



efficiency
150lm/W

LUMILEDS
LEDs

minimalist
design

luminous flux
4500lm i 9000lm

waterproof
IP66

L70B50
70.000h

degree of
protection IK08

surge protection
30W: 4/6KV, 60W: 6/10KV

aluminum housing
ADC12

PARK LUMINAIRE

NOLINA

Efficiency,
reliability for years

Energy savings, longer life and lower maintenance costs are key advantages that ensure a quick return on investment with our new park luminaire.

Shape

The luminaire, with its transparent polycarbonate shade and aluminum housing has a classic lantern shape that fits well in any space. The black color of the luminaire blends perfectly with our lighting pole.

Reliability



Durability of 70,000 h (L70B50), IP66, IK08 waterproofing and power supply with surge protection guarantee long and trouble-free operation. The warranty is 5 years.

Mounting flexibility

Mounting on lighting poles (Ø56-80 mm), including a split pole from our offer. The length of the power cord of power supply is 55 cm.

Usage

The luminaire is designed to illuminate paths, parks, squares and parking lots in public and private spaces, such as housing estates.



Available NOLINA park luminaire models:

207127	Park luminaire NOLINA 30W 4000K 4500lm
207134	Park luminaire NOLINA 60W 4000K 9000lm

5-years warranty	100°	MAX -25 + 50	voltage 220-240V AC	150 lm W	PF 0,9	IP66
ULOR 10%	SMD LED	tempered glass	DIE-CAST alu	IK 08		

