



IP44 Ceiling Light

It's perfect wherever you need it!

Ceilings from the LED Line LITE IP44 series are products that combine versatility with optimal lighting quality. They are suitable both for private homes and for large investments.

Whether you need lighting outside a building, at doors and gates, or inside for corridors, stairwells, or passageways, these fixtures will meet expectations in terms of both functionality and aesthetics.

The availability of ten indices allows you to tailor the lighting to specific needs, ensuring optimal lighting efficiency.



Symbol	Product name		Wattage	Luminous flux	Colour temperature	Version with sensor
201354	LED line LITE Ceiling Light II	P44	12W	900lm	3000K	_
201361	LED line LITE Ceiling Light II	P44	12W	900lm	3000K	×
201378	LED line LITE Ceiling Light II	P44	12W	960lm	4000K	_
201385	LED line LITE Ceiling Light II	P44	12W	960lm	4000K	×
201392	LED line LITE Ceiling Light II	P44	18W	1450lm	3000K	_
201408	LED line LITE Ceiling Light II	P44	18W	1450lm	3000K	×
201415	LED line LITE Ceiling Light II	P44	18W	1550lm	4000K	_
201422	LED line LITE Ceiling Light II	P44	18W	1550lm	4000K	×
201439	LED line LITE Ceiling Light II	P44	24W	1950lm	4000K	_
201446	LED line LITE Ceiling Light II	P44	24W	1950lm	4000K	×

Main product features:

- Luminous efficacy of 75 85lm/W,
- Available in 3 power types (12W, 18W, and 24W),
- Round shape with diameters ø260mm, 350mm, and 380mm,
- Color temperature of 4000K (12W/18W/24W) and 3000K (12W/18W),
- Versions with microwave motion sensor (360 degrees, 6 meters),
- IP44 protection rating,
- · Color rendering index Ra>80,
- 3-year warranty.

