

LED line PRIME

Code: 217027

EAN: 5905378217027

ESTADIO 200W 5000K 90° 170lm/w  
CRI80 PRIME



New

The stadium ESTADIO 200W is an advanced lighting solution characterized by light performance of 170 lm/W. Thanks to the colour of the light 5000 K and the colour rendering factor CRI 80, it provides excellent lighting quality. IP66 leak class and IK10 resistance guarantee durability under difficult external conditions. Powered by 100-277 V AC voltage, the housing offers a low PF power factor of 0.95.

100-277V AC

5 WARRANTY

MAX -40+45°C

IK 10

IP 66

PF 0,95

CE

Technical data

Parameter	Value	Parameter	Value
Warranty	5	CRI colour rendering index	80
Power	• 200 W	Beam angle	90
Voltage	• 100-227 V AC	LED type	EMC5050
Correlated colour temperature	• 5000 K	LED quantity	100
Colour of the light	White	Power Factor	0,95
IP protection rating	IP66	Lamp's warm-up time to 60%	0,5 s
IK protection rating	10	Ambient temperature suitable for operation	-40 / +45
IEC protection class	I	For indoor use	Outside
Luminous efficacy	170	Length	388
Luminous flux	34000	Width	305
The lumen maintenance factor	96	Height	150
Lifetime L70B50	100 000 h	Weight	4500
Colour consistency in McAdam ellipses	≤6	Material (housing)	Aluminium
Frequency of the supply voltage	50/60Hz	Material (cover)	polycarbonate

LED line PRIME


Code: 217027

EAN: 5905378217027

ESTADIO 200W 5000K 90° 170lm/w  
CRI80 PRIME

Technical drawing


Light distribution



Additional product photos




Logistics data




Single packaging

Weight	5 kg
--------	------



Bulk packaging

Quantity	5
Weight	



Europallet

---

LED line PRIME

Code: 217027

EAN: 5905378217027

**ESTADIO 200W 5000K 90° 170lm/w  
CRI80 PRIME**

---

**Example application**