

LED line PRIME

Code: 245435

EAN: 5901583245435

LED line downlight waterproof round  
die cast aluminium chrome

The PRIME LED line ceiling housing is a modern lighting element made of high quality materials, including matt glass and aluminum. It is characterized by a maximum energy of 35 W and a diameter of 83 mm, allowing adjustment of the 50 mm light source. Class III ensures safety of use and IP44 protection protects against moisture. The product is easy to install with a hole of 73 mm diameter.



Technical data

Parameter	Value
Warranty	5
IEC protection class	III
Maximum suitable lamp power	35 W
Fixture's diameter	83
Lamp's diameter	50 mm
Type of surface suitable for installation	F
Distance from illuminated surface	0.5 m

Parameter	Value
Installation method	recessed
Mounting hole diameter	73
Height	55
Colour	chrome
Material (housing)	Die cast aluminium
Material (cover)	Frosted glass


LED line PRIME

Code: 245435

EAN: 5901583245435

LED line downlight waterproof round  
die cast aluminium chrome

Technical drawing




Light distribution

Additional product photos




Logistics data




Single packaging

Width	91 mm
Height	61 mm
Length	91 mm
Weight	0,16 kg



Bulk packaging

Quantity	50
Width	0 mm
Height	0 mm
Length	500 mm
Volume	0 m3
Weight	8,15 kg
Comments	



Europallet

Quantity	1750
Height	1800 mm
Quantity in layer	7
Number of layers	5
Bulk quantity	35
Weight	283,5 kg

---

LED line PRIME

Code: 245435

EAN: 5901583245435

**LED line downlight waterproof round  
die cast aluminium chrome**

---

**Example application**