

LED line PRIME Code: 202368 EAN: 5905378202368

## LED bulb E27 1800K 4W 230lm 230V 360° FILAMENT G125 DIM Glass PRIME





LED bulb E27 4W 1800K 230Im Pillar G125 by LED line PRIME is an ideal combination of classic style and modern technology. Its colour temperature of 1800 K emits a warm, pleasant light, creating a relaxing atmosphere. Thanks to its high light performance of 57,5 Im/W and a durability of up to 25,000 hours, it is a long-term solution with low power consumption.











#### **Technical data**

Parameter	Value
Energy efficiency class 2019/2015	G
Warranty	5
Power	• 4 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 1800 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
Luminous efficacy	57,5
Luminous flux	230 lm
The lumen maintenance factor	96
Lifetime L70B50	25 000 h
Survival factor	0.9
Dimmable function	Triac
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz


Parameter	Value
Lamp's type	G125
Fixture's diameter	125 mm
Beam angle	360 °
LED type	Filament
LED quantity	1
Lifespan	25 000 h
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Height	175
Weight	101
Material	Glass
Material (housing)	Glass
Material (cover)	glass



LED line PRIME Code: 202368 EAN: 5905378202368

## LED bulb E27 1800K 4W 230lm 230V 360° FILAMENT G125 DIM Glass PRIME

#### **Technical drawing**




#### **Light distribution**


#### Additional product photos






#### Logistics data







### Single packaging

Quantity	1	
Width	50 mm	
Height	105 mm	
Length	50 mm	
Weight	0,11 kg	

### Bulk packaging

Quantity	20
Width	540 mm
Height	210 mm
Length	685 mm
Volume	0,077 m3
Weight	4,82 kg

### Europallet

Height	1890 mm
Quantity in layer	40
Number of layers	9
Bulk quantity	360
Weight	76,86 kg



LED line PRIME Code: 202368 EAN: 5905378202368

# LED bulb E27 1800K 4W 230lm 230V 360° FILAMENT G125 DIM Glass PRIME

#### **Example application**

