

LED line PRIME

Code: 203754-DALI

EAN: 5905378221550

**LINKER hermetic fixture 4000K 40W
6000lm IP65 120cm black PRIME DALI**



The LINKER 40W 4000K 6000lm fixture is characterized by a high luminous efficiency of 150 lm/W. Thanks to its IP65 protection class, it is fully protected against dust and water, allowing it to be used in harsh conditions. Its total lifespan exceeds 100,000 hours of operation and its IK08 impact resistance make it highly reliable.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	C
Warranty	5
Power	• 40 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP65
IK protection rating	08
IEC protection class	I
Luminous efficacy	150
Luminous flux	6000
The lumen maintenance factor	96
Lifetime L70B50	100 000 h
L80B* – difference B10–B50 ≈ 1% (according to LightingEurope) – negligible	75000 h
L90B* – difference B10–B50 ≈ 1% (according to LightingEurope) – negligible	50000 h
Dimmable function	Dali

Parameter	Value
Frequency of the supply voltage	50/60Hz
Beam angle	120
LED type	SMD2838
Lifespan	100 000 h
Power Factor	>=0,95
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-25 ÷ 45
Length	1191 mm
Width	72 mm
Height	61 mm
Weight	1,55 kg
Colour	Grey
Material (housing)	Polycarbonate
Material (cover)	Polycarbonate
DALI	• YES

LED line PRIME


Code: 203754-DALI

EAN: 5905378221550

**LINKER hermetic fixture 4000K 40W
6000lm IP65 120cm black PRIME DALI**

Technical drawing




Light distribution



Additional product photos



Logistics data



Single packaging

Quantity	1
Width	75 mm
Height	65 mm
Length	1120 mm
Weight	1,64 kg

Bulk packaging

Quantity	15
Width	355 mm
Height	246 mm
Length	1238 mm
Volume	
Weight	30,4 kg

Europallet

Quantity	180
Height	1500 mm
Quantity in layer	
Number of layers	
Bulk quantity	12
Weight	390 kg

LED line PRIME

Code: 203754-DALI

EAN: 5905378221550

**LINKER hermetic fixture 4000K 40W
6000lm IP65 120cm black PRIME DALI**

Example application

