

LED line PRIME Code: 201774 EAN: 5905378201774

## LED bulb E27 7W 6500K 1000lm 170-250V G45 globe PRIME





LED bulb E27 7W 6500K 1000lm from LED line PRIME is an innovative light source that combines high performance with elegant design. Thanks to the use of SMD2835 diodes, it achieves efficiency of 142 lm/W and a light stream of 1000 lumens. Colour temperature of 6500 K generates cool, white light, ideal for different interiors. With a durability of up to 30,000 hours and no flickering effect (SVM = 0.













#### **Technical data**

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	5
Power	• 7 W
Voltage	• 170-250 V AC
Correlated colour temperature	• 6500 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
Luminous efficacy	142
Luminous flux	1000
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Survival factor	0.9
Dimmable function	PWM
Colour consistency in McAdam ellipses	≤6

Parameter	Value
Frequency of the supply voltage	50/60Hz
Lamp's type	G45
Fixture's diameter	45 mm
Beam angle	220
LED type	SMD2835
Power Factor	0,5
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1s
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Height	84
Colour	White
Material	Ceramic
Material (housing)	Ceramics
Material (cover)	glass



LED line PRIME Code: 201774 EAN: 5905378201774

# LED bulb E27 7W 6500K 1000lm 170-250V G45 globe PRIME

#### **Technical drawing**


#### **Light distribution**



#### Additional product photos




### Logistics data




## Single packaging

Quantity	1
Width	50 mm
Height	63 mm
Length	50 mm
Weight	0,06 kg



#### Bulk packaging

Quantity	100
Width	270 mm
Height	230 mm
Length	530 mm
Volume	0,032 m3
Weight	7 ka



#### Europallet

Height	1840 mm
Quantity in layer	400
Number of layers	8
Bulk quantity	3200
Weight	224 kg

# MORE EFFICIENCY FOR THE LED WORLD



LED line PRIME Code: 201774 EAN: 5905378201774

# LED bulb E27 7W 6500K 1000lm 170-250V G45 globe PRIME

**Example application**