

LED line PRIME

Code: 202641

EAN: 5905378202641

**FLOODLIGHT 4000K 600W 84000lm 60°
IP66 PRIME**



LED line PRIME Floodlight 600 W and 84000 lm is an efficient light source with high efficiency. It is characterized by 60° light angle, allowing precise lighting of selected areas. It has IP66 leak class and IK08 impact resistance, making it ideal for applications in difficult weather conditions.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	5/7*
Power	• 600 W
Voltage	• 100-277 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	70
IP protection rating	IP66
IK protection rating	08
IEC protection class	I
Luminous efficacy	140
Luminous flux	84000
Lifetime L70B50	50 000 h

Parameter	Value
L80B* – difference B10–B50 ≈ 1% (according to LightingEurope) – negligible	35000 h
Wire length	930 mm
Frequency of the supply voltage	50/60Hz
Beam angle	60
LED type	SMD2835
LED quantity	1008
Ambient temperature suitable for operation	-40÷45
Length	575 mm
Width	530 mm
Height	65 mm
Material (housing)	Aluminium
Material (cover)	Tempered glass


LED line PRIME

Code: 202641

EAN: 5905378202641

**FLOODLIGHT 4000K 600W 84000lm 60°
IP66 PRIME**

Technical drawing




Light distribution

Additional product photos



Logistics data



Single packaging

Width	622 mm
Height	62,5 mm
Length	520 mm
Weight	10,2 kg

Bulk packaging

Quantity	1
Width	665 mm
Height	85 mm
Length	600 mm
Volume	0,033 m3
Weight	10,2 kg
Comments	

Europallet

Quantity	36
Height	1870 mm
Quantity in layer	2
Number of layers	22
Bulk quantity	44
Weight	25 kg

LED line PRIME

Code: 202641

EAN: 5905378202641

**FLOODLIGHT 4000K 600W 84000lm 60°
IP66 PRIME**

Example application