

LED line PRIME

Code: LL-12-24

EAN: 5907777479174

Power Supply 12-24 IP67 12W 24V
PRIME



LED line power supply PRIME 12-24 IP67 24V is an advanced device with high parameters. The input voltage is 90-264 V AC and the output voltage is 24 V DC. Its efficiency reaches 79%, which ensures efficient use of energy. With a maximum output current up to 0.5 A, the power supply is also characterized by a power factor PF of 0.95. Thanks to IP67 protection class is resistant to water and dust.

5
WARRANTY

IP
67

PF
0,95

24V
DC

MAX
-30÷70°C

CE

Technical data

Parameter	Value	Parameter	Value
Warranty	5	Voltage tolerance	-/+5.0%
Power	• 12 W	Ambient humidity	20 ÷ 90%
Voltage	• 90-264 V AC	Insulation strength	3kVAC
IEC protection class	II	EMC standards	EN55015
Output current range	0 ÷ 0.5A	Mounting type	surface
Input voltage frequency range	47 ÷ 63Hz	Inrush current (typ.)	6A / 230VAC
Rated current	0,5A	Ambient temperature suitable for operation	-30÷70
Safety standards	IP67	Output voltage	• 24 V
Efficiency	0,79		


LED line PRIME

Code: LL-12-24

EAN: 5907777479174

Power Supply 12-24 IP67 12W 24V
PRIME

Technical drawing




Light distribution

Additional product photos



Logistics data




Single packaging

Quantity	1
Width	41 mm
Height	27 mm
Length	165 mm
Weight	0,13 kg



Bulk packaging

Quantity	100
Width	290 mm
Height	230 mm
Length	345 mm
Weight	14,5 kg



Europallet

Quantity	3200
Height	1020 mm
Bulk quantity	32
Weight	474 kg

LED line PRIME

Code: LL-12-24

EAN: 5907777479174

Power Supply 12-24 IP67 12W 24V
PRIME

Example application