

LED line LITE


Code: 202887

EAN: 5905378202887

**Backlit Panel 4000K 40W 4000lm IP20
60x60cm white LITE**



LED Backlit 40W 4000K panel from LED line LITE is an advanced lighting fittings, which is distinguished by its high energy efficiency and robust performance. Thanks to the use of SMD LEDs 2835 the panel generates a light stream of 4000 lm at 40 W, which provides excellent lighting with minimal energy consumption. IP20 leak class and durable aluminium housing guarantee reliability of use.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	F
Warranty	3
Power	• 40 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	02
IEC protection class	II
Luminous efficacy	100
Luminous flux	4000
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6

Parameter	Value
Frequency of the supply voltage	50/60Hz
Beam angle	120
LED type	SMD LED 2835
LED quantity	48
Power Factor	0,9
Number of on/off cycles	25000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-25÷45
For indoor use	Inside
Length	595 mm
Width	595 mm
Height	28 mm
Weight	1,1 kg
Colour	white
Material (housing)	Aluminium
Material (cover)	Polystyrene


LED line LITE

Code: 202887


EAN: 5905378202887

**Backlit Panel 4000K 40W 4000lm IP20
60x60cm white LITE**

Technical drawing






Light distribution



Additional product photos



Logistics data



Single packaging

Quantity	1
Width	595 mm
Height	28 mm
Length	595 mm
Weight	1,3 kg

Bulk packaging

Quantity	10
Width	320 mm
Height	620 mm
Length	620 mm
Volume	0,123 m3
Weight	13 kg
Comments	

Europallet

Quantity	70
Height	1,90 m
Quantity in layer	
Number of layers	
Bulk quantity	7
Weight	120 kg

LED line LITE

Code: 202887

EAN: 5905378202887

**Backlit Panel 4000K 40W 4000lm IP20
60x60cm white LITE**

Example application

