

LED line PRIME

Code: 202948

EAN: 5905378202948

**FLOODLIGHT 3CCT (3K/4K/5K) 50W  
7000lm 30° IP66 PRIME**



The 50W PRIME Floodlight LED line is characterized by high light performance, reaching 7,000 lumens at 140 lm/W efficiency. It has a light distribution angle of 30°, allowing precise directing of the light stream. IP66 leak class and high impact resistance (IK08) make the device ideal for operation in difficult weather conditions.



**Technical data**

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	5/7*
Power	• 50 W
Voltage	• 100-277 V AC
Correlated colour temperature	• 3000 K • 4000 K • 5000 K
Colour of the light	CCT
Colour rendering index Ra	70
IP protection rating	IP66
IK protection rating	08
IEC protection class	I
Luminous efficacy	140
Luminous flux	7000
The lumen maintenance factor	96
Lifetime L70B50	50 000 h
L80B* – difference B10–B50 ≈ 1% (according to LightingEurope) – negligible	35000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6

Parameter	Value
Wire length	920 mm
Mounting type	surface
Frequency of the supply voltage	50/60Hz
Beam angle	30
LED type	SMD2835
LED quantity	96
Power Factor	0,9
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-40÷45
Length	252
Width	213
Height	43,5
Weight	1
Material (housing)	Aluminium
Material (cover)	Tempered glass

LED line PRIME

Code: 202948


EAN: 5905378202948

**FLOODLIGHT 3CCT (3K/4K/5K) 50W  
7000lm 30° IP66 PRIME**

**Technical drawing**



**Light distribution**



**Additional product photos**

**Logistics data**



**Single packaging**

Width	252 mm
Height	43,5 mm
Length	213 mm
Weight	1,85 kg

**Bulk packaging**

Quantity	5
Width	395 mm
Height	305 mm
Length	300 mm
Volume	0,036 m3
Weight	9,6 kg
Comments	

**Europallet**

Quantity	200
Height	1830 mm
Quantity in layer	40
Number of layers	6
Bulk quantity	240
Weight	460,8 kg

---

LED line PRIME

Code: 202948

EAN: 5905378202948

**FLOODLIGHT 3CCT (3K/4K/5K) 50W  
7000lm 30° IP66 PRIME**

---

**Example application**