

LED line LITE Code: 243929 EAN: 5901583243929

## LED bulb G4 3000K 35W 140lm 12V AC/DC 120° LITE





LED line LITE G4 2W 3000K 140lm is an energy-efficient LED bulb that is characterized by a light stream of 140 lumens at 2W power. It emits a warm, white light with a colour temperature of 3000 K, ideal for creating a cozy atmosphere. Thanks to the high colour rendering coefficient Ra ≥80 and a wide light angle of 120°, it provides natural color reproduction and uniform light scattering. The lifetime of the product is as much as 50,000 hours.



#### **Technical data**

Parameter	Value
Energy efficiency class 2019/2015	G
Energy class	A+
Warranty	2
Power	• 2 W
Voltage	• 12 V AC/DC
Correlated colour temperature	• 3000 K
Colour of the light	White
Colour rendering index Ra	80
Luminous efficacy	70
Luminous flux	140 lm
The lumen maintenance factor	96

Parameter	Value
Lifetime L70B50	50 000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Fixture's diameter	19 mm
Beam angle	120°
Lifespan	50 000 h
Number of on/off cycles	50000
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Height	30



LED line LITE Code: 243929 EAN: 5901583243929


# LED bulb G4 3000K 35W 140lm 12V AC/DC 120° LITE

**Technical drawing** 

**Light distribution** 


#### Additional product photos

#### Logistics data




#### Single packaging

Quantity	1
Width	30 mm
Height	9 mm
Length	42 mm
Weight	0,002 kg



#### **Bulk packaging**

Quantity	1000
Width	610 mm
Height	235 mm
Length	150 mm
Volume	0,021 m3
Weight	3,88 kg
Comments	



#### **Europallet**

Quantity	54000
Height	1880 mm
Quantity in layer	8000
Number of layers	8
Bulk quantity	64000
Weight	248,32 kg

### MORE EFFICIENCY FOR THE LED WORLD



LED line LITE Code: 243929 EAN: 5901583243929

## LED bulb G4 3000K 35W 140lm 12V AC/DC 120° LITE

**Example application**