

LED line PRIME

Code: 471055

EAN: 5907777471055

LED line downlight waterproof round
die cast aluminium black



The LED line Prime ceiling setting offers modern solutions in indoor and outdoor lighting. It is characterized by elegant design thanks to a matt glass lens and a solid aluminium cast housing, which ensures durability and aesthetics. It has IP44 seal class, which makes it resistant to moisture. It is easily mounted in holes with a diameter of 73 mm and the application of adjustment of the angle of light increases functionality.



Technical data

Parameter	Value
Warranty	5
IEC protection class	III
Maximum suitable lamp power	35 W
Fixture's diameter	83
Lamp's diameter	50 mm
Type of surface suitable for installation	F
Distance from illuminated surface	0.5 m

Parameter	Value
Installation method	recessed
Mounting hole diameter	73
Height	55
Colour	Czarny
Material (housing)	Die cast aluminium
Material (cover)	Frosted glass


LED line PRIME

Code: 471055

EAN: 5907777471055

LED line downlight waterproof round
die cast aluminium black

Technical drawing



Light distribution

Additional product photos




Logistics data




Single packaging

Width	91 mm
Height	71 mm
Length	91 mm
Weight	0,16 kg



Bulk packaging

Quantity	50
Width	0 mm
Height	0 mm
Length	500 mm
Volume	0 m3
Weight	8,15 kg
Comments	



Europallet

Quantity	1200
Height	1800 mm
Quantity in layer	2
Number of layers	6
Bulk quantity	12
Weight	216 kg

LED line PRIME

Code: 471055

EAN: 5907777471055

**LED line downlight waterproof round
die cast aluminium black**

Example application