

LED line PRIME Code: 201132 EAN: 5905378201132

LED line PRIME Ceiling lamp ACTON 24W 2600lm 4000K IP54 round





ACTON 24W LED Plafon is an advanced lighting luminaire that generates 2600 lumens of light. It is characterized by a neutral colour of light 4000K, ideal for use in different spaces. Thanks to IP54 leak class and IK08 resistance, the housing ensures durability and reliability in all conditions. High light efficiency of 108 Im/W and long working time of up to 30,000 hours guarantee economic use for many years.

















Technical data

Parameter	Value
Energy efficiency class 2019/2015	F
Warranty	5
Power	• 24 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP54
IK protection rating	08
IEC protection class	II
Luminous efficacy	108
Luminous flux	2600
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Survival factor	0.9


Parameter	Value
Dimmable function	PWM
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Fixture's diameter	280
Beam angle	120
LED type	SMD2835
Power Factor	0,9
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-25÷40
Height	51
Weight	750
Colour	White
Material (housing)	Polycarbonate
Material (cover)	Polycarbonate




LED line PRIME Code: 201132 EAN: 5905378201132

LED line PRIME Ceiling lamp ACTON 24W 2600lm 4000K IP54 round

Technical drawing



Light distribution



Additional product photos











Logistics data






Width	280 mm
Height	280 mm
Length	60 mm
Weight	0,9 kg



Bulk packaging

Quantity	10
Width	310 mm
Height	300 mm
Length	615 mm
Volume	0,057 m3
Weight	9,35 kg



Europallet

Quantity	200
Height	1,70 m
Quantity in layer	40
Number of layers	5
Bulk quantity	20
Weight	212 kg

MORE EFFICIENCY FOR THE LED WORLD



LED line PRIME Code: 201132 EAN: 5905378201132

LED line PRIME Ceiling lamp ACTON 24W 2600lm 4000K IP54 round

Example application