

LED line PRIME

Code: 206519

EAN: 5905378206519

**Panel Backlit 34W 4000K 4760lm
UGR<19 120x30 PRIME**



Backlit LED line PRIME panel with a power of 34 W and a colour of light 4000 K is an advanced lighting setting, providing a light stream of 4760 lm. Thanks to the backlit technology, the SMD LEDs 2835 placed in the housing allow uniform light transmission, resulting in excellent colour reproduction ($R_a \geq 80$). The panel has a lifespan of L70B50 up to 50,000 hours and a low glare ratio of UGR<19, which increases comfort of use.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	5
Power	• 34 W
Voltage	• 200-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	03
IEC protection class	II
Luminous efficacy	140
Luminous flux	4760
The lumen maintenance factor	96
Lifetime L70B50	50 000 h
Survival factor	0.9

Parameter	Value
Dimmable function	PWM
Colour consistency in McAdam ellipses	≤ 6
Frequency of the supply voltage	50/60Hz
Beam angle	90
LED type	SMD LED 2835
LED quantity	72
Power Factor	0,9
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Height	28
Colour	white
Material (housing)	Aluminium
Material (cover)	Polystyrene


LED line PRIME

Code: 206519


EAN: 5905378206519

Panel Backlit 34W 4000K 4760lm
UGR<19 120x30 PRIME


Technical drawing




Light distribution



Additional product photos




Logistics data




Single packaging

Quantity	1
Width	32 mm
Height	305 mm
Length	1245 mm
Weight	1,56 kg



Bulk packaging

Quantity	5
Width	330 mm
Height	180 mm
Length	1265 mm
Volume	0,075 m3
Weight	10,5 kg
Comments	



Europallet

Quantity	70
Height	1450 mm
Quantity in layer	70
Number of layers	1
Bulk quantity	70
Weight	150 kg

LED line PRIME

Code: 206519

EAN: 5905378206519

**Panel Backlit 34W 4000K 4760lm
UGR<19 120x30 PRIME**

Example application

