

LED line LITE

Code: 201446

EAN: 5905378201446

LED line LITE Ceiling lamp PLAFON 24W
4000K 1950lm IP44 with motion sensor



LITE 24W 4000K LED Plafon is an advanced lighting setting, combining modern design with high functionality. By emitting a light stream reaching 1950 lumens, it provides optimal lighting in different spaces. IP44 leak class guarantees resistance to atmospheric effects, and light efficiency of 81 lm/W translates into lower energy consumption.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	F
Warranty	3
Power	<ul style="list-style-type: none">24 W
Voltage	<ul style="list-style-type: none">220-240 V AC
Correlated colour temperature	<ul style="list-style-type: none">4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP44
IEC protection class	I
Luminous efficacy	81
Luminous flux	1950
The lumen maintenance factor	96
Lifetime L70B50	30 000 h

Parameter	Value
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6
Hold time	30 s
Frequency of the supply voltage	50/60Hz
Fixture's diameter	380 mm
Beam angle	120
LED type	SMD 2835
LED quantity	28
Ambient temperature suitable for operation	-20÷40
Height	62
Weight	430
Colour	Glass Out


LED line LITE

Code: 201446


EAN: 5905378201446

LED line LITE Ceiling lamp PLAFON 24W
4000K 1950lm IP44 with motion sensor

Technical drawing




Light distribution



Additional product photos




Logistics data




Single packaging

Quantity	1
Width	420 mm
Height	420 mm
Length	70 mm
Weight	0,55 kg



Bulk packaging

Quantity	12
Width	470 mm
Height	440 mm
Length	860 mm
Volume	0,177 m3
Weight	6,95 kg
Comments	



Europallet

Height	1760 mm
Quantity in layer	12
Number of layers	4
Bulk quantity	48
Weight	27,8 kg

LED line LITE

Code: 201446

EAN: 5905378201446

**LED line LITE Ceiling lamp PLAFON 24W
4000K 1950lm IP44 with motion sensor**

Example application

