

LED line PRIME

Code: 242915

EAN: 5901583242915

LED line downlight round adjustable die cast aluminium white

The PRIME LED line ceiling housing is a modern lighting that combines elegance with functionality. Its round construction made of aluminium casting ensures durability and reliability. The matte white finish makes it perfect for a variety of interior arrangements. It offers the possibility to adjust the lighting angle to 45°. The IP20 class is designed for internal use. The guarantee of 5 years confirms the high quality of the product.



Technical data

Parameter	Value
Warranty	5
IP protection rating	IP20
IEC protection class	III
Maximum suitable lamp power	35 W
Fixture's diameter	92
Lamp's diameter	50 mm
Y-axis angle regulation	45

Parameter	Value
Type of surface suitable for installation	F
Distance from illuminated surface	0.5 m
Installation method	recessed
Mounting hole diameter	80
Height	30
Colour	white
Material (housing)	Die cast aluminium


LED line PRIME

Code: 242915

EAN: 5901583242915

LED line downlight round adjustable die cast aluminium white

Technical drawing




Light distribution

Additional product photos




Logistics data




Single packaging

Quantity	1
Width	90 mm
Height	90 mm
Length	40 mm
Weight	0,05 kg



Bulk packaging

Quantity	100
Width	520 mm
Height	220 mm
Length	420 mm
Volume	0,048 m3
Weight	10 kg
Comments	



Europallet

Quantity	2800
Height	1,8 m
Quantity in layer	700
Number of layers	4
Bulk quantity	28
Weight	258 kg

LED line PRIME

Code: 242915

EAN: 5901583242915

**LED line downlight round adjustable die
cast aluminium white**

Example application