

LED line LITE


Code: 227750

EAN: 5905378227750

LED SMD bulb 3CCT (3K/4K/6.5K) 4,9W
500lm 230V 60° INSERT fi50mm PC LITE



The LED line Insert 50 mm module in a lightweight plastic housing allows for the selection of light color using the CCT switch on the back panel, even just before installation. It offers a beam angle of 60° and a luminous flux of 500 lm, making it ideal for zone and accent lighting. The ability to choose the color in one module simplifies installation and reduces inventory levels. The product is covered by a 3-year warranty.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	E
Warranty	3
Power	• 4,9 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 3000-4000-6500
Colour of the light	CCT
Colour rendering index Ra	80
IP protection rating	IP20
Luminous efficacy	100
Luminous flux	500
The lumen maintenance factor	96 %
Lifetime L70B50	25 000 h

Parameter	Value
Survival factor	0,9
Colour consistency in McAdam ellipses	≤6
Supply voltage	220-240VAC
Frequency of the supply voltage	50/60Hz
Beam angle	60°
Power Factor	0,7
Ambient temperature suitable for operation	˘ -20 ~45
For indoor use	Inside
Height	25 mm
Fixture's diameter	50 mm
Weight	0,025 kg
Material (housing)	Polycarbonate


LED line LITE

Code: 227750

EAN: 5905378227750

LED SMD bulb 3CCT (3K/4K/6.5K) 4,9W
500lm 230V 60° INSERT fi50mm PC LITE

Technical drawing




Light distribution

Additional product photos




Logistics data




Single packaging

Width	55 mm
Height	37 mm
Length	55 mm
Weight	0,046 kg



Bulk packaging

Quantity	100
Width	295 mm
Height	202 mm
Length	248 mm
Weight	4,6 kg



Europallet

Quantity	8000
Height	1,8 m
Bulk quantity	80
Weight	400 kg

LED line LITE

Code: 227750

EAN: 5905378227750

**LED SMD bulb 3CCT (3K/4K/6.5K) 4,9W
500lm 230V 60° INSERT fi50mm PC LITE**

Example application