LED line PRIME   Code: 479600-AW3HAT   EAN: 5905378212213

LINKER TRI-PROOF 55W 4000K 8250lm 150lm/W IP65 150cm Emergency module 3H AT PRIME

Linker 55W from the PRIME LED line is an innovative 8250 lm LED luminaire, which provides effective lighting at just 55 W. The colour of light of 4000 K guarantees neutral white, ideal for a variety of spaces. The housing has a high light efficiency of 150 lm/W and IP65 protection class, making it resistant to water and dust.

IP 65 | IK 08 | PF 0,95 | 220-240V AC | 5 WARRANTY

CE

Technical data

Parameter	Value		Parameter	Value
Energy efficiency class 2019/2015	D		Colour consistency in McAdam ellipses	≤6
Warranty	5		ULOR	3 %
Power	• 55 W		Emergency module test	Autotest
Voltage	• 220-240 V AC		Operating time in emergency mode	3 h
Correlated colour temperature	• 4000 K		Frequency of the supply voltage	50/60Hz
Colour of the light	White		Beam angle	120
Colour rendering index Ra	80		Lifespan	100 000 h
IEC protection class	II		Number of on/off cycles	50000
Luminous efficacy	150		Lamp's warm-up time to 60%	1 s
Luminous flux	8250		Ambient temperature suitable for operation	`-25 ÷ 45
The lumen maintenance factor	96		Colour	Grey
Lifetime L70B50	100 000 h		Material (housing)	Polycarbonate
Survival factor	0.9		Material (cover)	polycarbonate
Dimmable function	PWM			

LED line PRIME   Code: 479600-AW3HAT   EAN: 5905378212213

# LINKER TRI-PROOF 55W 4000K 8250lm 150lm/W IP65 150cm Emergency module 3H AT PRIME

Technical drawing

Light distribution

Additional product photos

Logistics data

Single packaging

Width	70 mm
Height	1520 mm
Length	60 mm
Weight	1,7 kg

Bulk packaging

Quantity	12
Width	240 mm
Height	1520 mm
Length	280 mm
Volume	0,102 m3
Weight	20,75 kg

Europallet

Quantity	144
Height	1520 mm
Quantity in layer	144
Number of layers	1
Bulk quantity	144
Weight	249 kg

LED line PRIME   Code: 479600-AW3HAT   EAN: 5905378212213

LINKER TRI-PROOF 55W 4000K 8250lm 150lm/W IP65 150cm Emergency module 3H AT PRIME

Example application