

LED line PRIME


Code: 210226

EAN: 5905378210226

Waterproof fixture RANGER 25-55W
4000K 9900lm 150cm PRIME



RANGER 25-55W 4000K 9900lm is an efficient lighting solution, characterized by high class IP66 tightness and IK10 impact resistance. The use of LED technology provides a light stream of up to 9900 lumens with a power of 25 to 55 W. The product operates in the 220-240 V AC voltage range and its colour temperature is 4000 K.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	C
Warranty	5
Power	• 25-55 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP66
IK protection rating	10
IEC protection class	II
Luminous efficacy	180
Luminous flux	9900
The lumen maintenance factor	96
Lifetime L70B50	100 000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6

Parameter	Value
Frequency of the supply voltage	50/60Hz
Beam angle	120
LED type	SMD2835
LED quantity	372
Power Factor	0,9
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1 s
Ambient temperature suitable for operation	-25÷45
Length	1510
Width	79
Height	68
Weight	1520
Colour	Grey
Material (housing)	Polycarbonate
Material (cover)	polycarbonate

LED line PRIME


Code: 210226

EAN: 5905378210226

Waterproof fixture RANGER 25-55W
4000K 9900lm 150cm PRIME

Technical drawing


Light distribution



Additional product photos




Logistics data




Single packaging

Weight	1,511 kg
--------	----------



Bulk packaging

Quantity	9
Width	273 mm
Height	242 mm
Length	1532 mm
Weight	13,6 kg



Europallet

LED line PRIME

Code: 210226

EAN: 5905378210226

**Waterproof fixture RANGER 25-55W
4000K 9900lm 150cm PRIME**

Example application