

LED line LITE Code: 248818 EAN: 5901583248818

LED line Panel Easy Fix 18W 2700K 1570lm round





LED panel Easy Fix 18W 2700K 1570Im round from LED line LITE brand is a modern light source that offers performance of 87 lm/W. It emits a warm light color at 2700 K, providing a cozy atmosphere. Thanks to a large light angle of 120°, it effectively eliminates shadows. The product has a high colour reproduction coefficient of Ra ≥80 and a durability of up to 30,000 hours.



















Technical data

Parameter	Value
Energy efficiency class 2019/2015	E
Energy class	A++
Warranty	3
Power	• 18 W
Voltage	• 220-260 V AC
Correlated colour temperature	• 2700 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IEC protection class	II
Luminous efficacy	87
Luminous flux	1570
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6


Parameter	Value
Frequency of the supply voltage	50/60Hz
Fixture's diameter	215 mm
Beam angle	120
LGP	GLASS
LED type	SMD2835
LED quantity	84
Power Factor	0,7
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-5÷40
For indoor use	Inside
Mounting hole diameter	60-185
Height	13
Colour	white
Material (housing)	Polyamide
Material (cover)	Polystyrene



LED line LITE Code: 248818 EAN: 5901583248818


LED line Panel Easy Fix 18W 2700K 1570lm round

Technical drawing



Light distribution


Luminous [cd/klm]



Additional product photos




Logistics data




Single packaging

Quantity	1
Width	235 mm
Height	4 mm
Length	224 mm
Weight	0,49 kg



Bulk packaging

Quantity	20
Width	430 mm
Height	250 mm
Length	465 mm
Volume	0,049 m3
Weight	14,1 kg
Comments	



Europallet

Quantity	420
Height	1860 mm
Quantity in layer	120
Number of layers	4
Bulk quantity	480
Weight	324 kg

MORE EFFICIENCY FOR THE LED WORLD



LED line LITE Code: 248818 EAN: 5901583248818

LED line Panel Easy Fix 18W 2700K 1570lm round

Example application