

LED line LITE

Code: 200814

EAN: 5905378200814

Downlight MOLLY 24W 2350lm 3000K round LITE



LED line LITE Downlight MOLLY with 24W power and 2350 lm light stream is a solution that combines modern design with high energy efficiency. The colour temperature of 3000K provides warm, pleasant light, and the Ra>80 colour rendering rate guarantees the naturalness of the shades. IP20 and IK05 leak class provide adequate protection under different indoor conditions.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	3
Power	• 24 W
Voltage	• 170-260 V AC
Correlated colour temperature	• 3000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IEC protection class	II
Luminous efficacy	100
Luminous flux	2350
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6

Parameter	Value
Frequency of the supply voltage	50/60Hz
Fixture's diameter	220 mm
Beam angle	110
LED type	SMD LED 2835
LED quantity	120
Power Factor	0,5
Number of on/off cycles	20000
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Mounting hole diameter	190-210
Height	26
Weight	205
Colour	White
Material (housing)	Polycarbonate


LED line LITE

Code: 200814


EAN: 5905378200814

Downlight MOLLY 24W 2350lm 3000K
round LITE

Technical drawing




Light distribution



Additional product photos




Logistics data




Single packaging

Width	224 mm
Height	36 mm
Length	228 mm
Weight	0,2 kg



Bulk packaging

Quantity	40
Width	450 mm
Height	80 mm
Length	420 mm
Volume	0,015 m3
Weight	8,35 kg



Europallet

Height	1920 mm
Quantity in layer	80
Number of layers	24
Bulk quantity	1920
Weight	400,8 kg

LED line LITE

Code: 200814

EAN: 5905378200814

**Downlight MOLLY 24W 2350lm 3000K
round LITE**

Example application

