

LED line LITE

Code: 200739

EAN: 5905378200739

DOWNLIGHT MOLLY 3000K 5W 450lm
round IP20 White LITE



The round Downlight LED line LITE MOLLY with 5W power and a light stream of 450 lm offers a warm colour temperature of 3000 K, which provides a pleasant atmosphere. With the Ra>80 colour reproduction factor, the lighting reflects the colours naturally, and the 110° lighting angle allows uniform distribution of light.




Technical data

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	3
Power	• 5 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 3000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IEC protection class	II
Luminous efficacy	90
Luminous flux	450
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6


Parameter	Value
Frequency of the supply voltage	50/60Hz
Fixture's diameter	95 mm
Beam angle	110
LED type	SMD LED 2835
LED quantity	16
Power Factor	0,5
Number of on/off cycles	20000
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Mounting hole diameter	75-90
Height	26
Weight	53.4
Colour	White
Material (housing)	Polycarbonate

DOWNLIGHT MOLLY 3000K 5W 450lm
round IP20 White LITE

Technical drawing




Light distribution



Additional product photos




Logistics data




Single packaging

Width	101 mm
Height	39 mm
Length	99 mm
Weight	0,05 kg



Bulk packaging

Quantity	100
Width	550 mm
Height	82 mm
Length	560 mm
Volume	0,025 m3
Weight	8,6 kg



Europallet

Height	1886 mm
Quantity in layer	200
Number of layers	23
Bulk quantity	4600
Weight	395,6 kg

LED line LITE

Code: 200739

EAN: 5905378200739

**DOWNLIGHT MOLLY 3000K 5W 450lm
round IP20 White LITE**

Example application

