

LED line PRIME Code: 470249-II EAN: 5905378201705

LED bulb E14 4000K 9W 1170lm 230V 220° C37 DIM Ceramic PRIME





LED bulb E14 9W 4000K 1170lm from LED line PRIME is an innovative lighting solution. It offers a luminous flux of 1170 lumens with a minimum energy consumption of only 9 watts, which translates into excellent energy efficiency. Thanks to the TRIAC-type dimming function, the user can adjust the intensity of light to individual needs.













Technical data

Parameter	Value
Energy efficiency class 2019/2015	E
Warranty	5
Power	• 9 W
Voltage	• 170-250 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
Luminous efficacy	130
Luminous flux	1170 lm
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Survival factor	0.9
Dimmable function	Triac
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz


Parameter	Value
Lamp's type	C37
Fixture's diameter	37 mm
Beam angle	220 °
LED type	SMD2835
Compatible dimmer type	TRIAC
Power Factor	0,7
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Height	111
Colour	White
Material	Ceramic
Material (housing)	Ceramics
Material (cover)	glass




LED line PRIME Code: 470249-II EAN: 5905378201705

LED bulb E14 4000K 9W 1170lm 230V 220° C37 DIM Ceramic PRIME

Technical drawing



Light distribution



Additional product photos













Logistics data




Single packaging

Quantity	1
Width	68 mm
Height	142 mm
Length	68 mm
Weight	0,06 kg



Bulk packaging

Quantity	100
Width	270 mm
Height	255 mm
Length	500 mm
Volume	0,034 m3
Weight	7 kg
Comments	



Europallet

Quantity	25000
Height	1890 mm
Quantity in layer	600
Number of layers	7
Bulk quantity	4200
Weight	294 kg

MORE EFFICIENCY FOR THE LED WORLD



LED line PRIME Code: 470249-II EAN: 5905378201705

LED bulb E14 4000K 9W 1170lm 230V 220° C37 DIM Ceramic PRIME

Example application