

LED line PRIME

Code: 210523

EAN: 5905378210523

Track light LUMICANTO 6-20W CCT 36/60° white PRIME



Track light LUMICANTO 6-20W CCT 36/60° white from LED line PRIME is a modern light source that provides high lighting quality. Thanks to the COB-BRIDGELUX LED technology used and the Ra 90 colour reproduction factor, it offers excellent color rendering. The housing is characterized by IP20 and IK06 protection, which makes it resistant to mechanical damage.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	E
Warranty	5
Power	<div><ul style="list-style-type: none">6-20 W</div>
Voltage	<div><ul style="list-style-type: none">220-240 V AC</div>
Correlated colour temperature	<div><ul style="list-style-type: none">3000 K4000K6000 K</div>
Colour of the light	White
Colour rendering index Ra	90
IP protection rating	IP20
IK protection rating	06
IEC protection class	II
Luminous efficacy	do 105
Luminous flux	620-2000
The lumen maintenance factor	96
Survival factor	0,9
Colour consistency in McAdam ellipses	≤6
Mounting type	3 phase rail

Parameter	Value
Frequency of the supply voltage	50/60Hz
Fixture's diameter	100 mm
Beam angle	60/36
LED type	COB-BRIDGELUX
LED quantity	1
Lifespan	50 000 h
Power Factor	>0,7
Number of on/off cycles	25000
Ambient temperature suitable for operation	5÷40
For indoor use	Inside
Width	152
Height	164
Colour	White
Material (housing)	Aluminium
Material (cover)	clear glass

LED line PRIME

Code: 210523


EAN: 5905378210523

Track light LUMICANTO 6-20W CCT
36/60° white PRIME




Technical drawing

Light distribution

Additional product photos



Logistics data



Single packaging

Width	108 mm
Height	175 mm
Length	186 mm
Weight	0,67 kg

Bulk packaging

Quantity	20
Width	385 mm
Height	365 mm
Length	565 mm
Volume	0,079 m3
Weight	16,8 kg

Europallet

Height	1825 mm
Quantity in layer	80
Number of layers	5
Bulk quantity	400
Weight	368 kg

LED line PRIME

Code: 210523

EAN: 5905378210523

**Track light LUMICANTO 6-20W CCT
36/60° white PRIME**

Example application