

LED line LITE

Code: 203310

EAN: 5905378203310

**LUMINO Floodlight 4000K 50W 5000lm
120° IP65 LITE**



LUMINO 50W LED line LITE is an innovative solution with high light performance of 5,000 lumens at 50 W. Thanks to the colour of the light 4000 K offers natural, white lighting. The product is characterized by IP65 protection class, which provides resistance to dust and water, and IK05 protection level, guaranteeing durability and impact resistance.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	F
Warranty	3
Power	• 50 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	70
IP protection rating	IP65
IK protection rating	05
IEC protection class	I
Luminous efficacy	100
Luminous flux	5000
The lumen maintenance factor	96
Lifetime L70B50	25 000 h
Survival factor	0.9

Parameter	Value
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Beam angle	110
LED type	SMD LED
LED quantity	56
Power Factor	0,9
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Length	169
Width	183
Height	29
Weight	480
Material (housing)	Die cast aluminium
Material (cover)	Tempered glass


LED line LITE

Code: 203310


EAN: 5905378203310

**LUMINO Floodlight 4000K 50W 5000lm
120° IP65 LITE**

Technical drawing






Light distribution



Additional product photos



Logistics data



Single packaging

Quantity	1
Width	169 mm
Height	29 mm
Length	183 mm
Weight	0,45 kg

Bulk packaging

Quantity	20
Width	355 mm
Height	195 mm
Length	395 mm
Volume	0,027 m3
Weight	9,35 kg

Europallet

Height	1775 mm
Quantity in layer	240
Number of layers	5
Bulk quantity	1200
Weight	561 kg

LED line LITE

Code: 203310

EAN: 5905378203310

**LUMINO Floodlight 4000K 50W 5000lm
120° IP65 LITE**

Example application