

LED line LITE

Code: 203952

EAN: 5905378203952

Panel Backlit 2in1 40W 4000K 4000LM
295x1195 Black LITE



Backlit panel 2in1 40W 4000K 4000LM is a high quality LED line LITE lighting fittings, designed for modern spaces. With a power of 40 W and a light output of 100 lm/W, the panel generates a light stream of 4,000 lumens. It is characterized by a colour of light 4000 K, which provides neutral lighting. The case made of metal and polystyrene guarantees durability and design allows a variety of assembly methods.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	E
Warranty	2
Power	40 W
Voltage	220-240 V AC
Correlated colour temperature	4000K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	02
IEC protection class	I
Luminous efficacy	100
Luminous flux	4000
The lumen maintenance factor	96

Parameter	Value
Lifetime L70B50	30 000 h
Survival factor	0.9
Dimmable function	PWM
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Power Factor	0.9
Lamp's warm-up time to 60%	1 s
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Height	38
Material (housing)	Metal
Material (cover)	polystyrene

LED line LITE

Code: 203952

EAN: 5905378203952

Panel Backlit 2in1 40W 4000K 4000LM
295x1195 Black LITE


Technical drawing

Light distribution

Additional product photos




Logistics data




Single packaging

Width	1205 mm
Height	45 mm
Length	305 mm
Weight	1,68 kg



Bulk packaging

Quantity	4
Width	325 mm
Height	200 mm
Length	1225 mm
Volume	0,079 m3
Weight	7,02 kg



Europallet

Height	1950 mm
Quantity in layer	48
Number of layers	6
Bulk quantity	288
Weight	505,44 kg

LED line LITE

Code: 203952

EAN: 5905378203952

**Panel Backlit 2in1 40W 4000K 4000LM
295x1195 Black LITE**

Example application