

LED line LITE Code: 244506 EAN: 5901583244506

## LED bulb G4 3000K 2W 220lm 12V DC 270° Silicone LITE



LEDOM G4 2W 3000K LED line LITE bulb is a perfect combination of energy savings and high performance. Powered by 12V DC voltage, emitting a warm light at 3000 K, it creates a cozy atmosphere. A light stream of 220 lm and a light angle of 270° ensure effective light scattering. Thanks to SMD3014 diodes, it achieves light efficiency of 110 lm/W.













#### **Technical data**

Parameter	Value
Energy efficiency class 2019/2015	F
Energy class	A+
Warranty	2
Power	• 2 W
Voltage	• 12 V DC
Correlated colour temperature	• 3000 K
Colour of the light	White
Colour rendering index Ra	80
Luminous efficacy	110
Luminous flux	220 lm
The lumen maintenance factor	96
Lifetime L70B50	50 000 h

Parameter	Value
Survival factor	0.9
Colour consistency in McAdam ellipses	<b>≤</b> 6
Frequency of the supply voltage	50/60Hz
Fixture's diameter	13 mm
Beam angle	270°
Lifespan	50 000 h
Number of on/off cycles	50000
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Height	37
Material (housing)	Silicone



LED line LITE Code: 244506 EAN: 5901583244506

### LED bulb G4 3000K 2W 220lm 12V DC 270° Silicone LITE

#### **Technical drawing**

**Light distribution** 




#### Additional product photos









#### Logistics data






#### Single packaging

Quantity	1
Width	20 mm
Height	20 mm
Length	62 mm
Weight	0,005 kg



#### **Bulk packaging**

Quantity	500
Width	610 mm
Height	235 mm
Length	150 mm
Volume	0,021 m3
Weight	4,285 kg
Comments	



#### Europallet

Quantity	54000
Height	1880 mm
Quantity in layer	4000
Number of layers	8
Bulk quantity	32000
Weight	182,4 kg

## MORE EFFICIENCY FOR THE LED WORLD



LED line LITE Code: 244506 EAN: 5901583244506

# LED bulb G4 3000K 2W 220lm 12V DC 270° Silicone LITE

**Example application**