

LED line PRIME Code: 201927 EAN: 5905378201927

LED bulb MR16 6500K 5W 600lm 10-18V AC/DC 120° GU5,3 Ceramic PRIME





LED bulb MR16 5W 6500K 600lm from LED line PRIME is a modern light source with high performance. The emission of a bright white light at 6500 K colour temperature reflects the natural daylight. Thanks to SMD2835 technology and a light stream of 600 lumens, it achieves light efficiency of 120 lm/W at only 5 W.









Technical data

Parameter	Value
Energy efficiency class 2019/2015	E
Warranty	5
Power	• 5 W
Voltage	• 10-18 V AC/DC
Correlated colour temperature	• 6500 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
Luminous efficacy	120
Luminous flux	600 lm
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6

Parameter	Value
Frequency of the supply voltage	50/60Hz
Lamp's type	MR16
Fixture's diameter	50 mm
Beam angle	120 °
LED type	SMD2835
Power Factor	0,5
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-5+40
For indoor use	Inside
Height	50
Colour	White
Material	Ceramic
Material (housing)	Ceramics




LED line PRIME Code: 201927 EAN: 5905378201927

LED bulb MR16 6500K 5W 600lm 10-18V AC/DC 120° GU5,3 Ceramic PRIME

Technical drawing



Light distribution





Additional product photos






Logistics data







Single packaging

Quantity	1
Width	20 mm
Height	20 mm
Length	62 mm
Weight	0,06 kg

Bulk packaging

Quantity	100
Width	280 mm
Height	145 mm
Length	575 mm
Volume	0,023 m3
Weight	7 kg

Europallet

Height	1950 mm
Quantity in layer	400
Number of layers	13
Bulk quantity	5200
Weight	364 kg



LED line PRIME Code: 201927 EAN: 5905378201927

LED bulb MR16 6500K 5W 600lm 10-18V AC/DC 120° GU5,3 Ceramic PRIME

Example application

