

LED line PRIME


Code: 203105

EAN: 5905378203105

LED line PRIME Road luminaire CAMINO  
50W 4000K 7000lm



CAMINO 50W LED line PRIME is an innovative lighting solution that stands out with a power of 50 W and a light stream of 7000 lumens. Thanks to high light efficiency of 140 lm/W and the use of LUMILEDS LEDs, it guarantees reliable operation. It offers neutral colour temperature 4000 K and IP66 leak classification provides resistance to adverse weather conditions.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	C
Warranty	5
Power	• 50 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	70
IP protection rating	IP66
IK protection rating	08
IEC protection class	I
Luminous efficacy	140
Luminous flux	7000
The lumen maintenance factor	96
Lifetime L70B50	100 000 h
Survival factor	0.9

Parameter	Value
Colour consistency in McAdam ellipses	≤6
ULOR	0 %
Frequency of the supply voltage	50/60Hz
Beam angle	150 x 110
LED type	LUMILEDS 2835
LED quantity	96
Power Factor	0,9
Lamp's warm-up time to 60%	1 s
Ambient temperature suitable for operation	-40÷50
Length	514
Width	200
Height	80
Material (housing)	Die cast aluminium
Material (cover)	tempered glass

LED line PRIME


Code: 203105

EAN: 5905378203105

LED line PRIME Road luminaire CAMINO  
50W 4000K 7000lm

Technical drawing


Light distribution



Additional product photos




Logistics data




Single packaging

Width	236 mm
Height	116 mm
Length	560 mm
Weight	2,3 kg



Bulk packaging

Quantity	1
Width	236 mm
Height	116 mm
Length	560 mm
Volume	15,33 m <sup>3</sup>
Weight	2,3 kg



Europallet

Height	1840 mm
Number of layers	1
Bulk quantity	96
Weight	330,4 kg

---

LED line PRIME

Code: 203105

EAN: 5905378203105

**LED line PRIME Road luminaire CAMINO  
50W 4000K 7000lm**

---

**Example application**