

LED line PRIME


Code: 475855

EAN: 5907777475855

LED line PRIME FUSION linear lamp
40W 4000K 5200lm 0-10V 60*110° black



FUSION LED line PRIME 40W and 4000K colour temperature provides an impressive light stream of 5200 lm. Thanks to high light efficiency of 130 lm/W and excellent stability of parameters, this solution fits into modern lighting standards perfectly. The 60° x 110° light distribution angle allows optimal adjustment to different spaces.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	C
Warranty	5
Power	• 40 W
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	08
IEC protection class	I
Luminous efficacy	130
Luminous flux	5200
The lumen maintenance factor	96
Lifetime L70B50	50 000 h
Survival factor	0.9

Parameter	Value
Dimmable function	0-10
Colour consistency in McAdam ellipses	≤6
Sling length	200 cm
Standby power	0
Mounting type	mixed
Frequency of the supply voltage	50/60Hz
Power Factor	0,9
Lamp's warm-up time to 60%	1 s
Ambient temperature suitable for operation	-20÷45
For indoor use	Inside
Length	1158
Width	70
Height	52

LED line PRIME

Code: 475855


EAN: 5907777475855

LED line PRIME FUSION linear lamp
40W 4000K 5200lm 0-10V 60*110° black

Technical drawing






Light distribution



Additional product photos



Logistics data



Single packaging

Width	1158 mm
Height	52 mm
Length	70 mm
Weight	1,82 kg

Bulk packaging

Quantity	12
Width	1260 mm
Height	260 mm
Length	260 mm
Volume	0,085 m3
Weight	22,09 kg
Comments	

Europallet

Quantity	288
Height	1260 mm
Quantity in layer	144
Number of layers	1
Bulk quantity	144
Weight	265,2 kg

LED line PRIME

Code: 475855

EAN: 5907777475855

**LED line PRIME FUSION linear lamp
40W 4000K 5200lm 0-10V 60*110° black**

Example application