

LED line PRIME Code: 204034 EAN: 5905378204034

## LED line PRIME FUSION linear lamp 20W 4000K 2600lm P18° white



The FUSION 20W linear luminaire from the LED line PRIME is characterized by a modern design and high light efficiency of 2,600 lumens at 4000K colour temperature. Made of solid aluminum, it provides excellent heat discharge, which translates into long-term operation. The 120° light angle milk can be used to ensure uniform light distribution.

















#### **Technical data**

Parameter	Value
Energy efficiency class 2019/2015	С
Warranty	5
Power	• 20 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
IP protection rating	IP20
Luminous efficacy	130
Sling length	200 cm
Standby power	0
Colour consistency in McAdam ellipses	≤6
Luminous flux	2600
Survival factor	0.9
Lifetime L70B50	50 000 h

Parameter	Value
Mounting type	mixed
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
The lumen maintenance factor	96
Power Factor	0,9
Ambient temperature suitable for operation	-20÷45
For indoor use	Inside
IEC protection class	1
IK protection rating	08
Lamp's warm-up time to 60%	1s
Length	586
Width	70
Height	52



LED line PRIME Code: 204034 EAN: 5905378204034

### **LED line PRIME FUSION linear lamp** 20W 4000K 2600lm P18° white

**Technical drawing** 


**Light distribution** 

Additional product photos






#### Logistics data






#### Single packaging

Width	586 mm
Height	52 mm
Length	70 mm
Weight	1,14 kg



#### **Bulk packaging**

Quantity	12
Width	690 mm
Height	260 mm
Length	260 mm
Volume	0,046 m3
Weight	13,93 kg
Comments	



#### Europallet

Quantity	288
Height	1710 mm
Quantity in layer	48
Number of layers	6
Bulk quantity	288
Weight	672 kg

## MORE EFFICIENCY FOR THE LED WORLD



LED line PRIME Code: 204034 EAN: 5905378204034

# LED line PRIME FUSION linear lamp 20W 4000K 2600lm P18° white

**Example application**