

LED line LITE

Code: 201033

EAN: 5905378201033

DOWNLIGHT MOLLY 3000K 5W 450lm square IP20 White LITE



LED line LITE DOWNlight MOLLY 5W 450lm 3000K square is a perfect combination of modern design and energy efficiency. It is characterized by a power of 5 W, emitting a luminous flux of 450 lm, which provides excellent luminous performance of 90-110 lm/W. Color temperature of 3000 K guarantees pleasant, warm light, perfectly reflective colors thanks to the Ra >80 indicator.




Technical data

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	3
Power	• 5 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 3000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IEC protection class	II
Luminous efficacy	90
Luminous flux	450
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6


Parameter	Value
Frequency of the supply voltage	50/60Hz
LED type	SMD LED 2835
LED quantity	30
Power Factor	0,5
Number of on/off cycles	20000
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Mounting hole diameter	75-90
Length	95
Width	95
Height	26
Weight	63.2
Colour	White
Material (housing)	Polycarbonate

DOWNLIGHT MOLLY 3000K 5W 450lm
square IP20 White LITE

Technical drawing




Light distribution



Additional product photos




Logistics data




Single packaging

Width	95 mm
Height	26 mm
Length	95 mm
Weight	0,09 kg



Bulk packaging

Quantity	100
Width	390 mm
Height	220 mm
Length	525 mm
Volume	0,045 m3
Weight	8,6 kg



Europallet

Height	1760 mm
Quantity in layer	400
Number of layers	8
Bulk quantity	3200
Weight	275,2 kg

LED line LITE

Code: 201033

EAN: 5905378201033

**DOWNLIGHT MOLLY 3000K 5W 450lm
square IP20 White LITE**

Example application

