

LED line LITE


Code: 200876

EAN: 5905378200876

DOWNLIGHT MOLLY 3000K 18W 1750lm square IP20 White LITE



The 18W Downlight MOLLY LED setting is characterized by a modern and minimalist design, which perfectly fits in a variety of interiors. It offers a light stream of 1750 lm and a colour temperature of 3000 K, which provides pleasant, warm light. IP20 leak class protects against dust and Ra>80 colour reproduction factor guarantees natural color rendering.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	3
Power	• 18 W
Voltage	• 170-260 V AC
Correlated colour temperature	• 3000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IEC protection class	II
Luminous efficacy	100
Luminous flux	1750
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6

Parameter	Value
Frequency of the supply voltage	50/60Hz
LED type	SMD LED 2835
LED quantity	72
Power Factor	0,5
Number of on/off cycles	20000
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Mounting hole diameter	140-160
Length	170
Width	170
Height	26
Weight	0,165 kg
Colour	White
Material (housing)	Polycarbonate


LED line LITE

Code: 200876


EAN: 5905378200876

DOWNLIGHT MOLLY 3000K 18W 1750lm square IP20 White LITE

Technical drawing



Light distribution



Additional product photos



Logistics data



Single packaging

Quantity	1
Width	170 mm
Height	26 mm
Length	170 mm
Weight	0,22 kg

Bulk packaging

Quantity	60
Width	390 mm
Height	374 mm
Length	551 mm
Volume	0,036 m3
Weight	13,6 kg

Europallet

Quantity	1200
Height	1,9 m
Quantity in layer	240
Number of layers	5
Bulk quantity	20
Weight	302 kg

LED line LITE

Code: 200876

EAN: 5905378200876

**DOWNLIGHT MOLLY 3000K 18W 1750lm
square IP20 White LITE**

Example application

