

LED line LITE

Code: 203945

EAN: 5905378203945

Panel Backlit 2in1 40W 4000K 4000LM
295x1195 White LITE



Backlit panel 2in1 40W 4000K from LED line LITE is a unique lighting setting that provides excellent performance and high light efficiency of 100 lm/W. It generates a luminous flux of 4000 lm at only 40 W. Thanks to the use of SMD LEDs and innovative backlit design, the panel guarantees even lighting. The copper-steel casing is durable and IP20 seal class confirms its suitability for interiors.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	E
Warranty	2
Power	• 40 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	02
IEC protection class	I
Luminous efficacy	100
Luminous flux	4000

Parameter	Value
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Survival factor	0.9
Dimmable function	PWM
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Power Factor	0.9
Lamp's warm-up time to 60%	1 s
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Material (housing)	Metal
Material (cover)	polystyrene

LED line LITE


Code: 203945

EAN: 5905378203945

Panel Backlit 2in1 40W 4000K 4000LM
295x1195 White LITE


Technical drawing

Light distribution




Additional product photos

Logistics data




Single packaging

Width	1205 mm
Height	45 mm
Length	305 mm
Weight	1,68 kg



Bulk packaging

Quantity	4
Width	325 mm
Height	200 mm
Length	1225 mm
Volume	0,079 m3
Weight	8,1 kg



Europallet

Height	1800 mm
Quantity in layer	
Number of layers	
Bulk quantity	80
Weight	505,44 kg

LED line LITE

Code: 203945

EAN: 5905378203945

**Panel Backlit 2in1 40W 4000K 4000LM
295x1195 White LITE**

Example application