

LED line LITE


Code: 207479

EAN: 5905378207479

Park Luminaire PARKLITE 80-100-120W
CCT 9600-14400lm black LITE



PARKLITE 80-120W park mount combines modern LED technology with elegant black finish. Its impressive light stream of 9600 to 14400 lumens provides excellent lighting under different conditions. The device is characterized by a class of protection IP65 and IK08, which guarantees resistance to adverse weather conditions and mechanical damage.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	E
Power	80 W 100 W 120 W
Voltage	220-240 V AC
Correlated colour temperature	3000 K 4000 K 6000 K
Colour of the light	White
Colour rendering index Ra	80
IK protection rating	08
IEC protection class	I
Luminous efficacy	120
Luminous flux	9600-14400
Lifetime L70B50	25 000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6
ULOR	2,3 %

Parameter	Value
Wire length	400 mm
Frequency of the supply voltage	50/60Hz
Beam angle	100
LED type	SMD LED 2835
LED quantity	384
Power Factor	0,9
Lamp's warm-up time to 60%	1 s
Ambient temperature suitable for operation	-30÷50
Height	117
Weight	2190
Colour	96
Material (housing)	Aluminium
Material (cover)	tempered glass

LED line LITE


Code: 207479

EAN: 5905378207479

Park Luminaire PARKLITE 80-100-120W
CCT 9600-14400lm black LITE

Technical drawing


Light distribution



Additional product photos




Logistics data




Single packaging

Width	420 mm
Height	135 mm
Length	425 mm
Weight	2,25 kg



Bulk packaging

Quantity	4
Width	445 mm
Height	430 mm
Length	550 mm
Volume	0,105 m3
Weight	9,3 kg



Europallet

Height	1780 mm
Quantity in layer	8
Number of layers	4
Bulk quantity	32
Weight	74,4 kg

LED line LITE

Code: 207479

EAN: 5905378207479

**Park Luminaire PARKLITE 80-100-120W
CCT 9600-14400lm black LITE**

Example application