

LED line PRIME


Code: 479662

EAN: 5907777479662

LED line PRIME Linear fixture FUSION
60W 4000K 7800lm 0-10V 120*120°
black



FUSION 60W LED line PRIME is a perfect solution for demanding lighting applications. Generates a luminous flux of 7800 lm at 4,000 K, which ensures high efficiency at 130 lm/W. The distribution angle is 120° and the dimming function in the range of 0-10V allows flexible adjustment to individual needs.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	C
Warranty	5
Power	• 60 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	08
IEC protection class	I
Luminous efficacy	130
Luminous flux	7800
The lumen maintenance factor	96
Lifetime L70B50	50 000 h

Parameter	Value
Survival factor	0.9
Dimmable function	0-10
Colour consistency in McAdam ellipses	≤6
Sling length	200 cm
Mounting type	mixed
Frequency of the supply voltage	50/60Hz
Power Factor	0,9
Lamp's warm-up time to 60%	1 s
Ambient temperature suitable for operation	-20÷45
For indoor use	Inside
Length	1444
Width	70
Height	52

LED line PRIME

Code: 479662


EAN: 5907777479662

LED line PRIME Linear fixture FUSION
60W 4000K 7800lm 0-10V 120*120°
black

Technical drawing




Light distribution



Additional product photos




Logistics data




Single packaging

Width	1444 mm
Height	52 mm
Length	70 mm
Weight	1,97 kg



Bulk packaging

Quantity	12
Width	1550 mm
Height	260 mm
Length	260 mm
Volume	0,104 m3
Weight	23,89 kg
Comments	60



Europallet

Quantity	144
Height	1550 mm
Quantity in layer	144
Number of layers	1
Bulk quantity	144
Weight	286,8 kg

LED line PRIME

Code: 479662

EAN: 5907777479662

**LED line PRIME Linear fixture FUSION
60W 4000K 7800lm 0-10V 120*120°
black**

Example application