

LED line PRIME

Code: 201163

EAN: 5905378201163

LED line PRIME Ceiling lamp ACTON
18W 1900lm 3000K IP54 square with
motion sensor



ACTON Plafon from LED line PRIME is an advanced 18W lighting solution and 1900lm light stream, which provides excellent efficiency at 105-111lm/W. It is characterized by a temperature of 3000K light, creating a cozy atmosphere. Equipped with a microwave motion sensor with a range of 8 meters and IP54 protection, the housing guarantees reliability both indoors and outdoors.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	F
Warranty	5
Power	• 18 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 3000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP54
IK protection rating	08
IEC protection class	II
Luminous efficacy	105
Luminous flux	1900
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Survival factor	0.9

Parameter	Value
Dimmable function	PWM
Colour consistency in McAdam ellipses	≤6
Hold time	90 s
Stand-by dimming level	01.06.2023
Frequency of the supply voltage	50/60Hz
Fixture's diameter	220
Beam angle	120
LED type	SMD2835
Power Factor	0,9
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-25÷40
Height	51
Weight	620
Material (housing)	Polycarbonate
Material (cover)	Polycarbonate


LED line PRIME

Code: 201163


EAN: 5905378201163

LED line PRIME Ceiling lamp ACTON
18W 1900lm 3000K IP54 square with
motion sensor

Technical drawing




Light distribution



Additional product photos




Logistics data




Single packaging

Width	220 mm
Height	220 mm
Length	60 mm
Weight	0,72 kg



Bulk packaging

Quantity	20
Width	470 mm
Height	250 mm
Length	615 mm
Volume	0,072 m3
Weight	14,75 kg



Europallet

Quantity	400
Height	1750 mm
Quantity in layer	40
Number of layers	7
Bulk quantity	280
Weight	206,5 kg

LED line PRIME

Code: 201163

EAN: 5905378201163

**LED line PRIME Ceiling lamp ACTON
18W 1900lm 3000K IP54 square with
motion sensor**

Example application