

LED line PRIME

Code: 203709-CAW3HAT

EAN: 5905378217904

LINKER TRI-PROOF 30W 4000K 4500lm
150lm/W 220-240V IP65 120cm
Emergency module CAW3HAT PRIME



The LINKER 30W LED line PRIME is a modern light source with a power of 30 W, generating an impressive light stream of 4,500 lm. It is characterized by high light performance of 150 lm/W and light colour temperature 4000 K, which provides neutral, pleasant lighting. Thanks to the IP65 protection class, it is resistant to water and dust. The emergency operation time is up to 3 hours.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	D
Energy class	A+
Warranty	5
Power	• 30 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000K
Colour of the light	White
Colour rendering index Ra	80
IK protection rating	08
IEC protection class	II
Luminous efficacy	150
Luminous flux	4500
The lumen maintenance factor	96
Lifetime L70B50	100 000 h
Survival factor	0.9
Dimmable function	PWM
Colour consistency in McAdam ellipses	≤6

Parameter	Value
ULOR	3 %
Emergency module test	AUTOTEST
Operating time in emergency mode	3 h
Frequency of the supply voltage	50/60Hz
Beam angle	120
LED type	SMD2835
Lifespan	100 000 h
Power Factor	0,95
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1 s
Ambient temperature suitable for operation	-25 ÷ 45
Length	1180
Width	72
Height	61
Material (housing)	Polycarbonate
Material (cover)	polycarbonate

LED line PRIME

Code: 203709-CAW3HAT

EAN: 5905378217904

LINKER TRI-PROOF 30W 4000K 4500lm
150lm/W 220-240V IP65 120cm
Emergency module CAW3HAT PRIME


Technical drawing

Light distribution

Additional product photos




Logistics data




Single packaging

Width	70 mm
Height	1220 mm
Length	60 mm
Weight	1,5 kg



Bulk packaging

Quantity	15
Width	240 mm
Height	1220 mm
Length	280 mm
Volume	0,081 m3
Weight	18,35



Europallet

Quantity	180
Height	1220 mm
Quantity in layer	180
Number of layers	1
Bulk quantity	180
Weight	220,2 kg

LED line PRIME

Code: 203709-CAW3HAT

EAN: 5905378217904

**LINKER TRI-PROOF 30W 4000K 4500lm
150lm/W 220-240V IP65 120cm
Emergency module CAW3HAT PRIME**

Example application

