

LED line PRIME


Code: 205970-DALI

EAN: 5905378220065

**Backlit Panel 4000K 25W 4000lm IP20
60x60cm white PRIME DALI**



The PRIME 25W LED line panel is an innovative 595x595 mm ceiling luminaire, characterized by high quality workmanship and even light distribution. Thanks to the use of SMD LEDs 2835, the panel generates a light stream of 4000 lm at 160 lm/W efficiency. The light colour is 4000 K, providing neutral lighting. The housing guarantees a longevity of 50.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	C
Warranty	5
Power	• 25 W
Voltage	• 200-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	02
IEC protection class	II
Luminous efficacy	160
Luminous flux	4000
The lumen maintenance factor	96
Lifetime L70B50	50 000 h
Survival factor	0.9
Dimmable function	Dali
Colour consistency in McAdam ellipses	≤6

Parameter	Value
Frequency of the supply voltage	50/60Hz
Beam angle	120
LED type	SMD LED 2835
LED quantity	96
Power Factor	0,9
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Length	60 cm
Width	60 cm
Height	28
Colour	white
Material (housing)	Aluminium
Material (cover)	Polystyrene
DALI	• YES

LED line PRIME

Code: 205970-DALI



EAN: 5905378220065

**Backlit Panel 4000K 25W 4000lm IP20
60x60cm white PRIME DALI**




Technical drawing

Light distribution

Additional product photos



Logistics data



Single packaging

Quantity	1
Width	30 mm
Height	640 mm
Length	600 mm
Weight	1,41 kg

Bulk packaging

Quantity	5
Width	170 mm
Height	655 mm
Length	615 mm
Volume	0,075 m3
Weight	9,6 kg
Comments	

Europallet

Quantity	60
Height	1880 mm
Quantity in layer	25
Number of layers	2
Bulk quantity	60
Weight	115,2 kg

LED line PRIME

Code: 205970-DALI

EAN: 5905378220065

**Backlit Panel 4000K 25W 4000lm IP20
60x60cm white PRIME DALI**

Example application

