

LED line PRIME

Code: 200647

EAN: 5905378200647

**FLOODLIGHT 4000K 150W 21000lm 120°  
IP66 PRIME**



The PRIME Floodlight 150W LED line is an advanced light source with a colour temperature of 4000K, emitting an impressive light stream of 21000 lumens. It is characterized by high energy efficiency, achieving productivity of 140 lm/W. The IP66 class winner provides excellent resistance to atmospheric conditions. With a light distribution angle of 120°, it can evenly illuminate large spaces.



**Technical data**

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	5/7*
Power	• 150 W
Voltage	• 100-277 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	70
IP protection rating	IP66
IK protection rating	08
IEC protection class	I
Luminous efficacy	140
Luminous flux	21000
The lumen maintenance factor	96
Lifetime L70B50	50 000 h
L80B* – difference B10–B50 ≈ 1% (according to LightingEurope) – negligible	35000 h

Parameter	Value
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6
Mounting type	surface
Frequency of the supply voltage	50/60Hz
Beam angle	120
LED type	SMD2835
LED quantity	360
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Length	412
Width	360
Height	54
Material (housing)	Aluminium
Material (cover)	Tempered glass

LED line PRIME

Code: 200647


EAN: 5905378200647

**FLOODLIGHT 4000K 150W 21000lm 120°  
IP66 PRIME**

**Technical drawing**






**Light distribution**



**Additional product photos**



**Logistics data**



**Single packaging**

Width	412 mm
Height	54 mm
Length	360 mm
Weight	3,57 kg

**Bulk packaging**

Quantity	1
Width	550 mm
Height	82 mm
Length	560 mm
Volume	0,025 m3
Weight	3,57 kg
Comments	

**Europallet**

Quantity	54
Height	1,8 m
Quantity in layer	18
Number of layers	3
Bulk quantity	54
Weight	218 kg

---

LED line PRIME

Code: 200647

EAN: 5905378200647

**FLOODLIGHT 4000K 150W 21000lm 120°  
IP66 PRIME**

---

**Example application**