


LED line PRIME Code: 242939 EAN: 5901583242939

LED line downlight square adjustable die cast aluminium gold













Technical data

Parameter	Value
Warranty	5
IP protection rating	IP20
IEC protection class	III
Maximum suitable lamp power	35 W
Lamp's diameter	50 mm
Y-axis angle regulation	45
Type of surface suitable for installation	F
Distance from illuminated surface	0.5 m


Parameter	Value
Installation method	recessed
Mounting hole diameter	75
Length	84
Width	84
Height	25
Colour	gold
Material (housing)	Die cast aluminium



LED line PRIME Code: 242939 EAN: 5901583242939

LED line downlight square adjustable die cast aluminium gold

Technical drawing




Light distribution

Additional product photos







Logistics data









Single packaging

Width	100 mm
Height	105 mm
Length	40 mm
Weight	0,07 kg

Bulk packaging

Quantity	100
Width	460 mm
Height	220 mm
Length	520 mm
Volume	0,052 m3
Weight	10 kg
Comments	

Europallet

Quantity	2800
Height	1760 mm
Quantity in layer	200
Number of layers	8
Bulk quantity	1600
Weight	160 kg

MORE EFFICIENCY FOR THE LED WORLD



LED line PRIME Code: 242939 EAN: 5901583242939

LED line downlight square adjustable die cast aluminium gold

Example application