

LED line PRIME

Code: 242977

EAN: 5901583242977

Downlight square adjustable die cast aluminium white

The PRIME LED line ceiling housing in white casting is an elegant and modern lighting solution. Thanks to the movable design with adjustable lighting angle in the y-axis, you will perfectly adjust the direction of light to your needs. Made of high quality materials ensures durability and reliability for long years of use. IP20 leak class allows installation inside buildings, and the socket dedicated to 50 mm light sources facilitates installation.



Technical data

Parameter	Value
Warranty	5
IP protection rating	IP20
IEC protection class	III
Maximum suitable lamp power	35 W
Lamp's diameter	50 mm
Y-axis angle regulation	45
Type of surface suitable for installation	F
Distance from illuminated surface	0.5 m

Parameter	Value
Installation method	recessed
Mounting hole diameter	75
Length	84
Width	84
Height	25
Colour	white
Material (housing)	Die cast aluminium


LED line PRIME

Code: 242977

EAN: 5901583242977

Downlight square adjustable die cast aluminium white

Technical drawing



Light distribution

Additional product photos




Logistics data




Single packaging

Quantity	1
Width	100 mm
Height	105 mm
Length	40 mm
Weight	0,07 kg



Bulk packaging

Quantity	100
Width	460 mm
Height	220 mm
Length	520 mm
Volume	0,052 m3
Weight	10 kg
Comments	



Europallet

Quantity	2100
Height	1760 mm
Quantity in layer	200
Number of layers	8
Bulk quantity	1600
Weight	160 kg

LED line PRIME

Code: 242977

EAN: 5901583242977

**Downlight square adjustable die cast
aluminium white**

Example application