

LED line LITE

Code: 205598

EAN: 5905378205598

Panel Backlit 2in1 40W 4000K 4000LM
620x620 White



Backlit panel 2in1 with a power of 40 watts and light colour temperature 4000 K is an excellent lighting solution. By emitting a luminous flux of 4000 lm, it provides efficiency at 100 lm/W. The backlit design guarantees uniform distribution of light, while the metal and polystyrene housing is resistant to deformation. Thanks to IP20 leak class and UGR index<22, the product offers high visual comfort.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	E
Warranty	2
Power	• 40 W
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	02
IEC protection class	I
Luminous efficacy	100
Luminous flux	4000
The lumen maintenance factor	96
Lifetime L70B50	30 000 h

Parameter	Value
Survival factor	0.9
Dimmable function	PWM
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Beam angle	120
Power Factor	0.9
Lamp's warm-up time to 60%	1 s
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Height	38
Material (housing)	Metal
Material (cover)	polystyrene

LED line LITE

Code: 205598

EAN: 5905378205598

Panel Backlit 2in1 40W 4000K 4000LM
620x620 White


Technical drawing

Light distribution

Additional product photos




Logistics data




Single packaging

Width	630 mm
Height	45 mm
Length	630 mm
Weight	1,67 kg



Bulk packaging

Quantity	6
Width	645 mm
Height	300 mm
Length	655 mm
Volume	0,128 m3
Weight	10,32 kg



Europallet

Height	1820 mm
Quantity in layer	24
Number of layers	2
Bulk quantity	48
Weight	82,56 kg

LED line LITE

Code: 205598

EAN: 5905378205598

**Panel Backlit 2in1 40W 4000K 4000LM
620x620 White**

Example application