

LED line PRIME

Code: 203136

EAN: 5905378203136

LED line PRIME Road luminaire CAMINO  
200W 4000K 28000lm



CAMINO 200W LED line PRIME is an outstanding light performance of 140 lm/W and a total stream of 28,000 lm. Equipped with high quality LUMILEDS diodes, it provides long-lasting and reliable operation. IP66 leak class and robust design made of toughened glass and aluminium guarantee resistance to difficult weather conditions.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	5
Power	• 200 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	70
IP protection rating	IP66
IK protection rating	08
IEC protection class	I
Luminous efficacy	140
Luminous flux	28000
The lumen maintenance factor	96
Lifetime L70B50	100 000 h
Survival factor	0.9

Parameter	Value
Colour consistency in McAdam ellipses	≤6
ULOR	0 %
Frequency of the supply voltage	50/60Hz
Beam angle	150 x 110
LED type	LUMILEDS 2835
LED quantity	320
Power Factor	0,9
Lamp's warm-up time to 60%	1 s
Ambient temperature suitable for operation	-40÷50
Length	665
Width	290
Height	84
Material (housing)	Die cast aluminium
Material (cover)	tempered glass

LED line PRIME


Code: 203136

EAN: 5905378203136


LED line PRIME Road luminaire CAMINO  
200W 4000K 28000lm

Technical drawing


Light distribution



Additional product photos




Logistics data




Single packaging

Width	665 mm
Height	84 mm
Length	290 mm
Weight	4,6 kg



Bulk packaging

Quantity	1
Width	3360 mm
Height	1160 mm
Length	7110 mm
Volume	27,71 m3
Weight	4,6 kg



Europallet

Height	1920 mm
Number of layers	1
Bulk quantity	48
Weight	284,2 kg

---

LED line PRIME

Code: 203136

EAN: 5905378203136

**LED line PRIME Road luminaire CAMINO  
200W 4000K 28000lm**

---

**Example application**