LED line PRIME   Code: 204539-AW3HAT   EAN: 5905378216655

Panel Backlit 34W CCT 4760lm UGR<19 62x62 emergency module 3h autotest PRIME

The LED backlit panel 34W CCT from LED line PRIME provides excellent light efficiency of 4760 lm. With an UGR ratio of <19, it is ideal for places requiring visual comfort. Thanks to the possibility of operating in emergency mode up to 3 hours and self-test function, it guarantees reliability in critical situations. Energy class C and life exceeding 50,000 hours emphasize its efficiency.

CE

Technical data

Parameter	Value
Energy efficiency class 2019/2015	C
Warranty	5
Power	• 34 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 3000 K • 4000 K • 5000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	02
IEC protection class	II
Luminous efficacy	140
Luminous flux	4760
The lumen maintenance factor	96
Lifetime L70B50	50 000 h
Survival factor	0.9
Dimmable function	Triac

Parameter	Value
Colour consistency in McAdam ellipses	≤6
Emergency module test	autotest
Operating time in emergency mode	3 h
Frequency of the supply voltage	50/60Hz
Beam angle	90
LED type	SMD LED 2835
LED quantity	128
Power Factor	0,9
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Height	30
Colour	White
Material (housing)	Aluminium
Material (cover)	Polystyrene

LED line PRIME   Code: 204539-AW3HAT   EAN: 5905378216655

## Panel Backlit 34W CCT 4760lm UGR<19 62x62 emergency module 3h autotest PRIME

Technical drawing   **Light distribution**

Additional product photos

Logistics data

Single packaging

Quantity	1
Width	35 mm
Height	640 mm
Length	630 mm
Weight	2,6 kg

Bulk packaging

Quantity	5
Width	200 mm
Height	640 mm
Length	650 mm
Volume	0,085 m3
Weight	12,7 kg
Comments	

Europallet

LED line PRIME   Code: 204539-AW3HAT   EAN: 5905378216655

Panel Backlit 34W CCT 4760lm UGR<19 62x62 emergency module 3h autotest PRIME

Example application