

LED line PRIME


Code: 210202

EAN: 5905378210202

Waterproof fixture RANGER 10-40W CCT 6000lm 120cm PRIME



RANGER 10-40W CCT 6000lm 120cm IP66 PRIME is an ideal solution for demanding users, providing high light performance of 150 lm/W. It is characterized by a durable polycarbonate housing and IP66 protection, which guarantees resistance to water and dust.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	5
Power	<div>• 10-40 W</div>
Voltage	<div>• 220-240 V AC</div>
Correlated colour temperature	<div><div>• 3000 K</div><div>• 4000K</div><div>• 5000 K</div></div>
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP66
IK protection rating	10
IEC protection class	II
Luminous efficacy	150
Luminous flux	6000
The lumen maintenance factor	96
Lifetime L70B50	100 000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6

Parameter	Value
Frequency of the supply voltage	50/60Hz
Beam angle	120
LED type	SMD2835
LED quantity	312
Power Factor	0,9
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1 s
Ambient temperature suitable for operation	-25÷45
Length	1210
Width	79
Height	68
Weight	1410
Colour	Grey
Material (housing)	Polycarbonate
Material (cover)	polycarbonate

LED line PRIME


Code: 210202

EAN: 5905378210202


Waterproof fixture RANGER 10-40W CCT  
6000lm 120cm PRIME

Technical drawing


Light distribution



Additional product photos




Logistics data




Single packaging

Weight	1,4 kg
--------	--------



Bulk packaging

Quantity	12
Width	316 mm
Height	273 mm
Length	1232 mm
Weight	16,8 kg



Europallet

---

LED line PRIME

Code: 210202

EAN: 5905378210202

**Waterproof fixture RANGER 10-40W CCT  
6000lm 120cm PRIME**

---

**Example application**