

LED line LITE

Code: 240560

EAN: 5901583240560

**Hermetic luminaire EASY LINK 4000K
40W 5600lm IP65 120cm gray LITE**



TRI-PROOF LED housing 40W 4000K Easy Link from LED line LITE is a modern solution with high light efficiency of 140 lm/W. It is characterized by a total luminous flux of 5600 lm and a neutral colour of light. Thanks to IP65 tightness class and IK08 impact resistance, it is ideal for use in difficult conditions.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	E
Warranty	3
Power	• 40 W
Voltage	• 175-265 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP65
IK protection rating	08
IEC protection class	II
Luminous efficacy	140
Luminous flux	5600
The lumen maintenance factor	96
Lifetime L70B50	35 000 h
Survival factor	0.9
Dimmable function	PWM
Colour consistency in McAdam ellipses	≤6
Mounting type	mixed

Parameter	Value
Frequency of the supply voltage	50/60Hz
CRI colour rendering index	80
Beam angle	160
LED type	SMD2835
LED quantity	324
Lifespan	35 000 h
Power Factor	0,95
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-25 ÷ 45
Length	1221
Width	74
Height	64
Weight	1109
Colour	white
Material (housing)	Polycarbonate
Material (cover)	Polycarbonate

LED line LITE


Code: 240560

EAN: 5901583240560

**Hermetic luminaire EASY LINK 4000K
40W 5600lm IP65 120cm gray LITE**



Technical drawing

Light distribution



Additional product photos

Logistics data



Single packaging

Quantity	1
Width	80 mm
Height	70 mm
Length	1280 mm
Weight	1,44 kg

Bulk packaging

Quantity	6
Width	270 mm
Height	160 mm
Length	1300 mm
Volume	0,056 m ³
Weight	8,64 kg
Comments	

Europallet

Quantity	120
Height	1444 mm
Quantity in layer	20
Number of layers	1
Bulk quantity	20
Weight	172,8 kg

LED line LITE

Code: 240560

EAN: 5901583240560

**Hermetic luminaire EASY LINK 4000K
40W 5600lm IP65 120cm gray LITE**

Example application