

LED line LITE

Code: 203341

EAN: 5905378203341

**LUMINO Floodlight 4000K 200W
20000lm 120° IP65 LITE**



LUMINO 200W LED line LITE is an advanced LED light that generates a light stream of as much as 20000 lm. At 4,000 K colour temperature, it provides neutral white light, perfectly complementing space. Thanks to the use of SMD LED technology and durable construction from aluminium casting and tempered glass, the product is characterized by low heat emission and high resistance to atmospheric conditions (IP65).



Technical data

Parameter	Value
Energy efficiency class 2019/2015	F
Warranty	3
Power	• 200 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	70
IP protection rating	IP65
IK protection rating	05
IEC protection class	I
Luminous efficacy	100
Luminous flux	20000
The lumen maintenance factor	96
Lifetime L70B50	25 000 h
Survival factor	0.9

Parameter	Value
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Beam angle	110
LED type	SMD LED
LED quantity	224
Power Factor	0,9
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Length	290 mm
Width	405 mm
Height	36 mm
Weight	2 kg
Material (housing)	Die cast aluminium
Material (cover)	Tempered glass


LED line LITE

Code: 203341


EAN: 5905378203341

**LUMINO Floodlight 4000K 200W
20000lm 120° IP65 LITE**

Technical drawing






Light distribution



Additional product photos



Logistics data



Single packaging

Quantity	1
Width	326 mm
Height	36 mm
Length	405 mm
Weight	2,2 kg

Bulk packaging

Quantity	2
Width	335 mm
Height	100 mm
Length	430 mm
Volume	0,014 m3
Weight	8,85 kg

Europallet

Quantity	400
Height	1,90 m
Quantity in layer	48
Number of layers	4
Bulk quantity	80
Weight	875 kg

LED line LITE

Code: 203341

EAN: 5905378203341

**LUMINO Floodlight 4000K 200W
20000lm 120° IP65 LITE**

Example application