

LED line PRIME

Code: 470560

EAN: 5907777470560

LED line® SMD 5W 6500K 400lm 220-260V 50mm



LED line bulb PRIME SMD 5W 6500K is a light source characterized by a light stream of 400 lumens and a colour temperature of 6500 K, generating cool, white light. With a light output of 80 lm/W and a durability of 30,000 hours, it is a cost-effective and ecological solution. The product made of ceramic and glass provides aesthetic appearance and high resistance to damage.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	G
Energy class	A+
Warranty	5
Power	• 5 W
Voltage	• 220-260 V AC
Correlated colour temperature	• 6500 K
Colour of the light	White
Colour rendering index Ra	80
IEC protection class	II
Luminous efficacy	80
Luminous flux	400
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Survival factor	0.9

Parameter	Value
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Fixture's diameter	50 mm
Beam angle	110
LED type	SMD2835
Power Factor	0,4
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1 s
Ambient temperature suitable for operation	-5÷40
For indoor use	Inside
Height	22
Colour	white
Material (housing)	Ceramics
Material (cover)	glass

LED line PRIME

Code: 470560


EAN: 5907777470560

LED line® SMD 5W 6500K 400lm 220-260V 50mm


Technical drawing




Light distribution



Additional product photos




Logistics data




Single packaging

Quantity	1
Width	50 mm
Height	50 mm
Length	60 mm
Weight	0,08 kg



Bulk packaging

Quantity	100
Width	290 mm
Height	170 mm
Length	595 mm
Volume	0,029 m3
Weight	7 kg
Comments	



Europallet

Quantity	4500
Height	1870 mm
Quantity in layer	400
Number of layers	11
Bulk quantity	4400
Weight	308 kg

LED line PRIME

Code: 470560

EAN: 5907777470560

**LED line® SMD 5W 6500K 400lm 220-
260V 50mm**

Example application